




MK3045

Schottky Bypass Diode Module



Features/

- High frequency operation /
- Low forward voltage drop/
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance /
- long term reliability/

Typical Applications/

Photovoltaic solar cell protection schottky rectifier/

Mechanical Data/

- **Package/** : GF030S
- Molding compound meets UL 94 V-0 flammability rating/ UL 94 V-0
- **Terminals/** : Tin plated leads, solderable per J-STD-002 and JESD 22-B102/ J-STD-002 JESD 22-B102
- **Polarity/** : As marked/

■ Maximum Ratings (Ta=25 Unless otherwise specified / (Ta=25))

PARAMETER	SYMBOL	UNIT	MK3045
Device marking code			MK3045
Repetitive Peak Reverse Voltage	VRRM	V	45
Average Rectified Output Current @60Hz half sine-wave, R-load, Ta=25 60Hz Ta=25	Io	A	30
Surge(Non-repetitive)Forward Current@60Hz half sine-wave, 1 cycle, Ta=25 () 60Hz Tj =25	IFSM	A	325
Current Squared Time @1ms≤t<8.3ms Tj=25 (1ms t<8.3ms Tj =25)	I²t	A²s	435
Storage Temperature	Tstg		-55 ~+150
Junction Temperature/ IN DC Forward Mode-Forward Operations without reverse bias, t ≤1 h (Fig. 1)(1) 1h 1	Tj		-55 ~+200

NOTE (1) Meets the requirements of IEC 61215 Ed. 2 bypass diode thermal test.
1 IEC 61215 ED.2

■ Electrical Characteristics Ta=25 Unless otherwise specified / (Ta=25)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	MK3045
Maximum instantaneous forward voltage drop per diode	VFM	V	IF=30A	0.55
Maximum DC reverse current at rated DC blocking voltage per diode	IRRM1	mA	VRM=VRRM Ta=25	0.1
	IRRM2		VRM=VRRM Ta=100	7.0
	IRRM3		VRM=VRRM Ta=125	20



MK3045

■ Thermal Characteristics $T_a=25$ Unless otherwise specified / ($T_a=25$)

PARAMETER	SYMBOL	UNIT	MK3045
Thermal Resistance 1	$R_{\theta J-C}$	/W	1.0

Note (1) Thermal resistance from Between junction and case, On glass-epoxi substrate.

(1) (1) Pn

■ Ordering Information (Example) / ()

PREFERRED P/N	UNIT WEIGHT(g) ()	MINIIMUM PACKAGE(pcs) ()	OUTER CARTON QUANTITY(pcs) ()	DELIVERY MODE
MK3045	Approximate 5.5 5.5 /	30	1500	Tube

■ Characteristics (Typical) / ()

FIG1: I_o -Tc Curve
 I_o -Tc




FIG2: Surge Forward Current Capability




FIG3: Forward Voltage






FIG4: Typical Reverse Characteristics





■Outline Dimensions /



DIM	MM		NOTE
	MIN	MAX	
A	10.5	11.5	
B	15.9	16.9	
C	11.6	12.6	
D	11.23	12.23	
E	25.5	26.5	
F	3.5	4.5	
G	6.5	7.5	
H	4.3	4.7	
I	16.5	17.5	
J	1.7	2.1	
K	5.1	5.7	
L	5.65	5.95	
M	4.4	5	
N	0.6	0.8	
O	14.73	15.13	
P	29.5	30.5	
Q	44.5	45.5	
R	2.35	2.65	
S	2	2.3	



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

[Redacted text block]

[Redacted text block]